

Models 2050, 2053, 2051
(6.5 R-VALUE*)

PREMIUM series



3-LAYER CONSTRUCTION



① Steel + ② Insulation + ③ Steel

6.5
R-VALUE*
1³/₈" insulation


PANEL OPTIONS



2050 (Short Elegant)



2053 (Long Elegant)



2051 (Flush)

COLORS



(Printed colors may vary from actual panel colors)

WINDOWS

- Short windows available on Models 2050 and 2051
- Long windows available on Models 2050, 2051, and 2053
- Plain Series and Snap-In Series (Colonial) windows are standard in 2nd section from top; all other windows standard in top section unless specified otherwise

Plain Series



Plain Short

Snap-In Series



Charleston 508

Wrought Iron Series



Tuscany

See pages S19–S20 for all available window designs and options.

WARRANTIES



PRODUCT SPECIFICATIONS

- 27 gauge steel skins and insulation are pressure bonded for durable, secure, quiet operation.
- 1³/₈" thick polystyrene insulation provides energy efficiency. **R-value 6.5***.
- Hot-dipped galvanized steel skin with a baked-on primer and top coat helps assure durability and long-lasting beauty.
- Nylon rollers for durable, smooth, long-lasting performance.
- Patented Safe-T-Bracket® designed for added safety; under normal circumstances it cannot be removed while the door is under tension.
- Tongue-and-groove joints and bottom weatherseal in a rust-proof aluminum retainer helps seal out the elements.
- 12" radius track for normal installations. 15" radius track available.
- Extension springs standard on all single doors (up to and including 10' wide). EZ-SET® torsion springs standard on double doors (greater than 10' wide).
- Inside slide lock is standard, outside keyed lock available (at additional charge).

STYLE AND FINISH

- Woodgrain texture raised and flush panel designs may be painted with a high quality exterior latex paint to complement any home's exterior.
- Prefinished white end stiles and interior steel provide a clean and finished appearance.

SIZES

- Models 2050 and 2051 available in 2" increments from 6' to 18' wide.
- Model 2053 available in 2" increments from 8' to 18' wide.
- Available in heights from 6' to 12' in 3" increments (excluding 7'3").
- For high lift track applications please call Clopay customer service.

SPECIAL NOTES

- For doors sold through Home Depot's Expert Installation Program, the springing systems and locking systems may vary by market.
- Doors ordered in white unless a color is specified.

*Calculated door section R-value is in accordance with DASMA TDS-163.

STANDARD HEADROOM REQUIREMENTS

Extension Springs		Torsion Springs	
Track Radius	Headroom Needed**	Track Radius	Headroom Needed**
12"	10"	12"	12"
15"	12"	15"	14"

**Add 3" for automatic garage door opener.