


# GALLERY® collection

## Models GR4SV, GR4LV (6.3 R-Value\*) Models GR4S, GR4L (24 Gauge)




Shown: Design GR4LV with LONG windows and SQUARE grilles

### 2-LAYER CONSTRUCTION 1<sup>5</sup>/<sub>16</sub>" Insulated



① Steel + ② Insulation

### 1-LAYER CONSTRUCTION Non-Insulated



① Steel (Non-Insulated)

## PRODUCT SPECIFICATIONS

- 2-layer construction (Steel + Insulation) on Models GR4SV, GR4LV. Non-insulated Models GR4S, GR4L.
- Heavy-duty 24 gauge patented deep emboss panel with a vertical ribbed pattern. 1<sup>5</sup>/<sub>16</sub>" polystyrene insulation available (Models GR4SV, GR4LV). R-value 6.3\*
- 2" thick frame secured to steel shell with a durable, rust-proof Tog-L-Loc® fastening system.
- Hot-dipped galvanized steel skin with a baked-on primer and top coat helps assure durability and long-lasting beauty.
- Nylon rollers for durable, smooth, long-lasting performance.
- Patented Safe-T-Bracket® designed for added safety; under normal circumstances it cannot be removed while the door is under tension.
- Shiplap joints and bottom weatherseal in a rust-proof aluminum retainer help seal out the elements.
- 12" radius track for normal installations. 15" radius track available.
- Extension springs standard on single doors (up to and including 10'). EZ-SET® torsion springs standard on all double doors (greater than 10' wide).
- Inside slide lock is standard, outside keyed lock available (at additional charge).
- Spade Lift Handles and Spade Step Plate are standard.

## STYLE & FINISH

- Patented deep emboss panel stamp is available in both the Short emboss panel (GR4SV, GR4S) and the Long emboss panel (GR4LV, GR4L) to complement any home's style.
- Finish may be painted to complement the home's exterior.
- Windows are made from 1/8" DSB or Obscure glass with optional Snap-In grilles. The window frames and grilles are UV-protected. Acrylic Wrought Iron windows also available.

## SIZES

- Available in heights from 6' to 12' in 3" increments.
- Models GR4SV and GR4S doors available in 2" wide increments from 6' to 20' wide.
- Models GR4LV and GR4L doors available in 2" wide increments from 7'8" to 20' wide.

### EXCEPTIONS

- Doors not available in widths from 10'2" through 11'4" or 14'8".
- Windows not available on 14'10" and 15'4" widths.
- **Door widths requiring single spade handle or Twisted "T" design keyed lock: 6'2", 6'4", 6'6", 7'8", 7'10", 11'6", 11'8", 11'10", 14'10" through 15'10" and 19'2" through 19'10".**

## SPECIAL NOTES

- For doors sold through Home Depot's Expert Installation Program, the springing systems and locking systems may vary by market.
  - Doors ordered in white unless a color is specified.
- \*Calculated door section R-value is in accordance with DASMA TDS-163.


## STANDARD HEADROOM REQUIREMENTS

Extension Springs		Torsion Springs	
Track Radius	Headroom Needed*	Track Radius	Headroom Needed*
12"	10"	12"	12"
15"	12"	15"	14"

\* Add 3" for automatic garage door opener

## MODELS

### Short Panel



GR4SV / GR4S

### Long Panel



GR4LV / GR4L

## COLORS



White



Almond



Desert Tan



Sandtone



Chocolate

(Printed colors may vary from actual panel colors)

Chocolate not available on GR4L and GR4LV

## WINDOWS / TOP SECTIONS



SHORT SOLID



LONG SOLID



SHORT PLAIN



SHORT SQUARE GRILLE



LONG PLAIN



LONG SQUARE GRILLE



ARCH WROUGHT IRON




LONG RECTANGLE GRILLE



SHORT WROUGHT IRON




LONG WROUGHT IRON




ARCH1 PLAIN



ARCH1 GRILLE



ARCH2 PLAIN



ARCH2 GRILLE



ARCH3 PLAIN



ARCH3 GRILLE



SHORT ASHFORD®



LONG ASHFORD®




SHORT CLAYTON™



LONG CLAYTON™



SHORT KRISTIN®



LONG KRISTIN®



SHORT TRENTON®



LONG TRENTON®

## DECORATIVE HARDWARE

### Standard Hardware:



Spade Lift Handles  
(4118684)



Spade Step Plate  
(4119015)

See page G4 for complete hardware options.

## WARRANTIES

